



RW-Z5

High Quality meets Affordability



Printing Method: Direct Thermal

Print Speed: Up to 6 ips

Resolution: 203 dpi

Processor: 32 bit

Command Set: ZPL & EPL compatible

Max Print Width: 4.09 inches

Max Print Length: 40 inches

Media Width: 0.63" ~ 4.7"

Media Core: 0.5" or 1.0"

Label Roll Capacity: 5" O.D.

Sensors: Transmissive Gap
Reflective Black Mark Printhead Open

Operator Panel: One function button
(Pause, Line Feed & Menu), One status LED

Real Time Clock: Factory Optional

Interface: USB 2.0
Ethernet 10/100 Mbps
RS-232 (optional)
Parallel (optional)
Bluetooth or WiFi (optional)

Character Set: 7 bitmap fonts, 1 vector font built-in.

Additional bitmap fonts. Hex, PCX, BMP & IMG files are downloadable.

Bitmap fonts can be enlarged 10x. Vector fonts - zoom without scale

Character rotation; 0, 90, 180, 270

Bar Code: Code 39, Code 93, Code128 (subsets A, B & C) Codabar, Interleave 2 of 5, Standard & Industrial 2 of 5, LOGMARS, Planet Code, EAN-8, EAN-13, UPC-A, UPC-E, UPC/EAN Extensions, GS1 DataBar (RSS) PDF-417, Micro PDF-417, Maxicode, DataMatrix, QR Code, GS1 Composite

Physical Dim: W6.8" x H6.6" x D8.3"

Weight: 3.7 lbs (printer)

Power: External Switching 120~240V

Environmental: Operating: 41~113oF, 90%RH (140oF)

Storage: -40~140oF, 93%RH (140oF)

Regulatory: UL / FCC

Warranty: Printer 2 years, Printhead 1 year

Accessories: *Included:* CD, Quick Start Guide, USB cable *Optional:* Peel Module, External media holder

Warranty: 2 years. PH 1 year

Corporate Headquarters

www.Chimeragroupinc.com

3370 N. San Fernando Road, Suite 202 LA, California 90065

P:(888) 383-6083 F:(888) 916-0164

