



multicard



CT4-LX-HC

4-inch Desktop Printer for Healthcare

Healthcare Dedicated

- Clinical-ready anti-microbial plastic casing
- Conducive for the use of disinfectant cleansers



Expedite Patient Workflows

- Specimen Labels
- Pharmacy Labels
- Bloodbag Labels
- Identification Wristbands



Efficient & Cost Effective

- On-board printer language emulations
- Auto-clone printer settings
Backup or duplicate settings on a USB flash drive
- PDF Direct Print
Print PDF formats directly from the printer, no driver required.



Functional Design

- One-touch media profile recall
Register settings of commonly printed label types.
- Label waste prevention
Print from the first label and eliminate label loss.
- 4.3" full-color touchscreen



www.satoamerica.com/CT4-LX-HC



GENERAL SPECIFICATIONS / CT4-LX-HC

| PRODUCT SPECIFICATIONS | | | |
|--------------------------------|-------------------|-------------------|-----------------------------|
| Print Resolution | | 203 dpi | 305 dpi |
| Print Speed | | 8 ips | 6 ips |
| Print Area | Max Width | 4.09" (104mm) | |
| | Max Length | 98.43" (2500mm) | 59.06" (1500mm) |
| Media Size (with liner) | Length | Standard | 0.98" - 4.65" (25 - 118mm) |
| | | Continuous | 0.39" - 15.74" (10 - 400mm) |
| | | Tear-off | 0.98" - 15.74" (25 - 400mm) |
| | | Cutter | 0.91" - 15.74" (23 - 400mm) |
| | | Dispenser | 0.91" - 15.74" (23 - 400mm) |

| PRINTING SPECIFICATIONS | CONNECTIVITY | BARCODE SYMBOLOGIES |
|---|--|---|
| Method Thermal Transfer (with Direct Thermal capability) | Standard USB 2.0 (Type A, Type B), Ethernet (DHCPv4/DHCPv6), NFC | Barcodes Linear Code 39, Code 93, Code 128, CODABAR (NW7), EAN8/13, GS1-Databar™, GS1-128 (UCC/EAN128), Interleaved 2/5, Industrial 2/5, JAN 8/13, Matrix 2/5, MS1, Bookland, Postnet™, UPC-A/E |
| Mode Continuous, Tear-off, Cutter, Dispenser | Optional Interfaces Wi-Fi and Bluetooth Ver 4.1 (Wi-Fi® and Wi-Fi Direct® Certified IEEE 802.11ac, Dual Band (2.4 GHz, 5 GHz)) | 2D Symbologies PDF417, Micro PDF, Maxi Code, GS1 Data Matrix, QR Code, Micro QR Code and Composite Symbologies, Aztec |
| MEDIA SPECIFICATIONS | MEMORY & PROCESSING | OPERATING CHARACTERISTICS |
| Sensor Type Transmissive Sensor for Gap, Reflective Sensor for Black Mark, Paper Out, Ribbon Out | Printer Memory 4GB Flash, 1GB RAM | Electrical Requirements AC100V ~ AC240V ± 10%, 50/60 Hz (AC adapter) Output: DC24V ± 5.0% 2.7A |
| Media Type Roll (Continuous, Die-cut), Fan-fold, Tag, Ticket | User Downloadable Fonts, Videos, Graphics or Format Maximum 1GB | Standards & Agency Approvals Please contact SATO regarding agency approvals in your region. |
| Media Thickness (Label & Liner) 0.0031" - 0.075" (0.08 - 0.19mm) | Large Status LED Blue / Red | Environment Operating 32 - 104°F (0 - 40°C) / 30 - 80% RH (without condensation) |
| Roll Diameter Maximum: 5.04" (128mm) on 1.5" core | Audible Alerts Adjustable Volume Setting | Storage 14 - 140°F (-10 - 60°C) / 15 - 90% RH (without condensation) |
| Wind Face-in / Face-out | Self Diagnosis Head Check, Stand-by Mode, Cover Open, Test Print, Auto-Calibration, Label End, Ribbon Near-End and End | PHYSICAL CHARACTERISTICS |
| Ribbon Length 328' (100m) on 0.5" ID Core | Display Panel 4.3" Full Color Resistive Touch Screen | Dimensions 9.37" L x 7.0" W x 8.43" H (238mm x 177.8mm x 214.1mm) |
| Width 1.77" - 4.37" (45 - 111mm) | Tool-Free Maintenance Print Head and Platen Replacement | Weight 7.5 lbs (3.4kg) |
| Roll Diameter 1.5" (40mm) | Multi-national Language Support 47 Printable Languages with Scalable Fonts 31 LCD menu languages | Finishing Disinfectant-ready and anti-microbial casing |
| Wind Face-out | Operation Videos Multiple Instructional Videos On-board, Space for Customized Videos | MISCELLANEOUS |
| SATO Genuine Consumables For maximum print quality and optimum use, SATO recommends the use of SATO genuine consumables. | Emulation Auto Detect - SBPL®, SEPL®, SZPL®, SDPL®, SIPL® or STCL® (Pre-installed), XML, PDF Direct Printing*, AEP* *Contact your SATO Sales Representative for more information/requirements | Functions - Useful Features Standalone Printing with SATO Application Enabled Printing (AEP), SATO Online Services (SOS), Multiple Interfaces-Auto-Switching, Auto Clone, Status Return, Label Waste Prevention |
| FONT SPECIFICATIONS | Remote Maintenance SNMP Ver. 3, Web Interfaces, SATO Online Services (SOS), All-In-One Tool (AIOT), SOTI Connect | Rotation Auto-label Rotation: 0°, 90°, 180°, 270° |
| Internal Fonts 16 Bitmap SATO Fonts, 40 Scalable SATO Fonts, Multi-National Language Support (47 Languages/Unicode), Single and Double Byte Fonts (Korean, Chinese, Japanese) | OPTIONS | |
| | Cutter, Real-Time Clock, Wireless LAN and Bluetooth | |

MULTICARD CORPORATE

4920 E McDowell
Road #101
Phoenix, AZ 85008
888-383-6083
info@multicard.com